

CYCLONE SERIES GAS CONVECTION OVENS



Model : BCO-G1

Model : BCO-G2

Design Features

- Energy efficient 60,000 BTUH oven combination direct/indirect forced air heat system in Natural & LP gas
- 120v, 60hz controls
- Electronic temperature control
- Stainless steel, 60/40 split independent doors, with dual mounted handles
- Stainless steel doors seals
- Double-pane thermal glass door windows
- Interior oven light
- 60-minute continuous ring timer with manual shut off
- 150°F (65°C) to 550°F (288°C) temperature range
- 1/4 HP air-cooled two-speed fan motor
- Cool down fan mode
- Burners-on and temperature-ready indicator lights
- Porcelain enamel oven interior
- 11-Position removable rack guide with 1 5/8" spacing
- 5 Heavy-duty, positive-stop, chrome-plated wire racks
- Black Powder Coated legs with adjustable bullet feet
- Stacking kit for double ovens
- Front mounted, hinged control panel for easy service access
- Heavy-duty industrial grade insulation in top, sides, back and doors
- Limited 1-year parts, labor and door warranty

Specifications

Full-size gas, forced air, single and double deck convection type oven. Standard specifications include 60,000 BTUH per deck, a two-speed fan with cool down and our patented wheel-within-a-wheel enhanced air flow system powered by an energy saving 1/4 HP air cooled fan motor.

Door interlock switch automatically turns the fan and burners off when the oven door is open. A manual rotary switch will turn the fan on when the door is open for quick cool-down. The 60 minute timer has a continuous ring alarm with manual shut-off. The indicator light glows when the burners are on.

The oven interior measures 29" wide (737mm) by 20" high (508mm) by 22 1/4" deep (567mm). The cooking chamber is porcelain enamel over heavy gauge steel with removable 11-position rack guides with 1 5/8" spacing (41mm) and 5 heavy-duty adjustable chrome-plated racks.

The Oven exterior measures 39" wide (991mm) by 39" deep with handles (991mm) and 41 3/8" deep with handles (1051mm) by 32" (813mm) high. Front, top, sides and trim are constructed with stainless steel. Single oven legs are 31 3/8" tall (797mm) with casters and 27 5/8" (702mm) with adjustable bullet feet and finished with Durable Black Powder Coating.

Dual doors are 60/40 split-type with double-pane thermal glass, independent operation, stainless steel seals and double mounted "Cool Touch" handles. Doors are fabricated with stainless steel inside-and-out, and fully insulated with 2" of industrial grade insulation. Units are hardwired, plug and cord are not included.


Options & Accessories

- Open rack stand with rack supports
- Black Powder coated legs with stainless steel undershelf
- Additional Oven Racks
- Heavy-duty caster set, two with casters locks
- Oven Flue
- Stainless steel legs with or without casters
- Solid Doors
- Perforated rear panel – field installation only
- International voltages

Certifications



CYCLONE SERIES GAS CONVECTION OVENS



ALL DIMENSIONS NOMINAL

SHIPPING INFORMATION										
Model	SHIPPING WEIGHT		CARTON DIMENSIONS						Crate size	
	Lbs	Kilos	Width		Depth		Height		Cubic Feet	Cubic Meter
			In	mm	In	mm	In	mm		
BCO-G1	565	256	43	1092	48 1/4	1226	38 1/2	972	39.25	1.11
BCO-G2	Double Shipped in two cartons as per above specifications									

Gas Supply – 1/2 NPT rear connection				
	Manifold Pressure		Inlet Pressure	
	WC	Mbar	WC	Mbar
Natural	3.5	9 min	7"	17.5 min
Propane	1	25	NA	NA

Separate gas connections or external manifold required for stacked ovens

POWER SUPPLY									
Model	BTUH	KW	HZ	Voltage	Amps	Wire	Phase	RMP-Low	RMP-High
BCO-G1	60,000	17.58	60	120	3.5	2	1	900	1,725

MINIMUM CLEARANCES				
	Vent Hood		Direct venting	
	Inches	mm	Inches	Mm
Left Side	1	25	3	76
Right Side	1	25	1	25
Rear	3	76	3	76

Suitable for installation on combustible floors when installed on factory supplied legs or casters

SPECIFICATIONS						
OVERALL DIMENSIONS						
Model	Width		Depth		Height	
	In	mm	In	mm	In	mm
BCO-G1	39	991	41 9/16"	1056	63 3/8"	1610
BCO-G2	39	991	41 9/16"	1056	72 1/4"	1835

Continuous product improvement is a policy of Bakers Pride Oven Company. Therefore, specifications and design are subject to change without notification