

STANDARD FEATURES

- DURABLE STAINLESS STEEL**
 Our megatops boast a sturdy stainless steel exterior and interior finish and galvanized back panel providing strength and durability.
- ERGONOMICALLY DESIGNED SOLID DOORS**
 Standard doors come with easy grip handles and self closing/120 ° stay open door feature, working together for customer convenience while ABS door liner provides thermal efficiency.
- MAGNETIC DOOR GASKET**
 Built of one piece, the gasket is removable without tools for ease of cleaning and replacement. Door's in step design gives added protection to the gasket.
- EFFICIENT REFRIGERATION SYSTEM**
 Factory engineered oversized and balanced refrigeration system. CFC-free R-134A Refrigerators maintain temperature from 33° to 41°F. Forced air design underneath pans to keep products fresh.
- FRONT BREATHING**
 Allows unrestricted placement of the unit.
- HIGH DENSITY POLYURETHANE INSULATION**
 2" CFC-free polyurethane insulation foamed in place for extra strength and energy efficiency, while being environmentally friendly with zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- INSULATED LIDS**
 Removable insulated lids keep food fresh and cold by reducing condensation.
- REVERSIBLE & EASY CLEANING CUTTING BOARD**
 The full length removable white polyethylene cutting board provides a comfortable 10" operation space.
- STANDARD WITH FULL SETS OF 1/6th PANS, 4" DEEP**
 * Except for the EDMT27: two of the pans are 1/9th size.
 It can also accommodate 6" deep pans.

OPTIONS & ACCESSORIES

Additional epoxy coated shelves / 2.5" Casters /
 6" Adjustable stainless steel legs / Factory reverse door hinging /
 220V-50 cycles-1 phase

Mega Top Tables

- EDMT27-12
- EDMT48-18

- EDMT60-24
- EDMT70-32



EDMT27-12



EDMT48-18



EDMT72-30




ISO 9001


MODEL	DOORS	TOP PANS	SHLVs.	AMPS	HP	VOLTAGE	NEMA PLUG	CORD LENGHT	CABINET DIMENSIONS			SHIPPING	
									L	D*	H**	Wt.	Cubes
REFRIGERATOR													
EDMT27-12	1	12	1	5.1	1/6	115/60/1	5-15P	8'	27"	34"	41-5/8"	225	36
EDMT48-18	2	18	2	6.0	1/4	115/60/1	5-15P	8'	48"	34"	41-5/8"	327	55
EDMT60-24	2	24	2	7.3	1/3	115/60/1	5-15P	8'	60"	34"	41-5/8"	380	73
EDMT72-30	3	30	3	8.0	1/3	115/60/1	5-15P	8'	72"	34"	41-5/8"	465	87

* Depth does not include 1" rear bumper **Height does not include 5" overall for casters


EDMT27-12 Top




EDMT48-18 Top




EDMT60-24 Top




EDMT70-32 Top




EDMT27-12 Front




EDMT48-18 Front




EDMT60-24 Front




EDMT70-32 Front




EDMT27-12 Common View



Open Lid



Closed Lid



* Specifications

■ CABINET CONSTRUCTION

- EXTERIOR: Stainless steel, galvanized steel back.
- INTERIOR: Stainless steel.
- CABINET & DOOR : Entire foamed-in-place high-density, CFC-free, polyurethane insulation. Coved corner floor to meet NSF requirements.
- CASTERS: 4" Diameter swivel casters, front two with brakes.
- SHELVES: 2 Adjustable heavy duty epoxy coated wire shelves per door.

■ DOORS

- Stainless steel exterior with ABS interior liner.
- One piece constructions magnetic gasket, removable without tools for easy cleaning.
- Self-closing doors with 120° stay open feature and recessed handles for convenient loading and unloading.

■ REFRIGERATION SYSTEM

- Oversized and balanced refrigeration system.
- R-134A holding temperature at 33°F to 41°F Refrigerators.
- Self-contained capillary tube system using environmentally-friendly and CFC-free refrigerant.
- Front breathing allows unrestricted placement of the unit.
- Evaporator coil is mounted in the rear of the unit with full accessibility from the back.
- Large fan motor and fan blades for better air circulation.
- Self contained system, no plumbing necessary.
- Access for the condensing unit behind the front grill, slides out for easy cleaning maintenance.

■ ELECTRICAL

- The whole unit is completely pre-wired at factory with cord and plug set included and ready for final connection to a 115/60/1 phase.
- 220V / 50Hz / 1Ph available from factory.

■ WARRANTY

Continental US & Canada :

- **One year** labor and parts warranty.
- **Five year** compressor warranty.
- **International:** one year parts only.