

Hinged Point of Sale Glass Door



VR-7-US (formerly JUNIOR-1-US)

Height 53.75"
Length 21"
Depth 23.63"
Cubic Ft. 7
Liters 198
Bottles (20 oz) 90
Cans (12oz) 216



VR-8-US (formerly V-252-US)

Height 59.13"
Length 21"
Depth 23.63"
Cubic Ft. 8
Liters 227
Bottles (20 oz) 120
Cans (12oz) 252



VR-12-US

Height 62"
Length 25.63"
Depth 22.75"
Cubic Ft. 12
Liters 340
Bottles (20 oz) 168
Cans (12oz) 384

Features

- Interior and exterior constructed of heavy-duty white coated steel
- Polyurethane insulation with cyclopentane as blowing agent
- Double paned glass door with Low-E protection to avoid condensation
- Illuminated top header sign (VR-8-US)
- Externally mounted hinged glass doors
- Recessed door handle
- Heavy duty shelves with clips
- Heavy duty hinges with self closing mechanism
- Forced air evaporator for quick temperature "Pull Down"
- Heavy duty condensing unit with R-134a refrigerant, located in front for easy access maintenance
- T-8 lighting system and electronic ballast provide a life expectancy of 24,000 hrs
- UL Classified to ANSI/NSF 7



VR-15-US

Height 64.75"
Length 30"
Depth 25.75"
Cubic Ft. 15
Liters 425
Bottles (20 oz) 192
Cans (12oz) 504

| Model No. | Description | Voltage | Amps | Temp | HP | Est. Ship Weight |
|-----------|------------------|---------|------|-------------|-----|------------------|
| VR-7-US | 1 Door/2 Shelves | 115 | 3.7 | 32°F - 39°F | 1/5 | 187# |
| VR-8-US | 1 Door/3 Shelves | 115 | 3.8 | 32°F - 39°F | 1/5 | 205# |
| VR-12-US | 1 Door/3 Shelves | 115 | 4.5 | 32°F - 39°F | 1/5 | 235# |
| VR-15-US | 1 Door/3 Shelves | 115 | 3.7 | 32°F - 39°F | 1/4 | 310# |

Technical Data / Glass Door



| Model # | VR-7-US | VR-8-US | VR-12-US | V-15-US |
|----------------------------|-----------------|----------------|----------------|--------------|
| Outside Dimensions | | | | |
| Depth | 23.625" | 23.63" | 22.75" | 25.75" |
| Length | 21" | 21" | 25.63" | 30" |
| Height | 53.75" | 59.13" | 62" | 64.75" |
| Door Size | 21.75" x 42.25" | 21.75" x 38.5" | 26.25" x 50.3" | 30" x 47.75" |
| Door Type | 1 swing | 1 swing | 1 swing | 1 swing |
| Inside Dimensions | | | | |
| Depth | 18" | 18" | 19" | 21.75" |
| Length | 17.5" | 17.5" | 22" | 25.14" |
| Height | 38.75" | 45" | 47.5" | 45.88" |
| Shelf Size | 16.75"x16.75" | 16.75"x16.75" | 21.25"x17.5" | 24.5"x19.5" |
| # of Shelves | 2 | 3 | 3 | 3 |
| Capacity: Cubic Foot | 7 | 8 | 12 | 15 |
| Specifications | | | | |
| Operating Temperature | 32°F-39°F | 32°F-39°F | 32°F-39°F | 32°F-39°F |
| Refrigerant | R-134a | R-134a | R-134a | R-134a |
| Compressor Size HP | 1/5 | 1/5 | 1/5 | 1/4 |
| Voltage | 115 | 115 | 115 | 115 |
| Amperage | 3.7 | 3.8 | 4.5 | 3.7 |
| Cord and Plug | yes | yes | yes | yes |
| Shipping Dimensions | | | | |
| Depth | 24" | 24" | 24" | 28" |
| Length | 23" | 23" | 27" | 32" |
| Height | 60" | 66" | 66" | 68" |
| Gross Weight lbs. | 187 | 205 | 235 | 310 |
| Cubic feet | 19 | 21 | 25 | 35 |

- Cases are designed to operate at 75°F and 55% relative humidity.
- Specification subject to change without notice.

