	Project Name:		AIA#:
Model #:	, <u> </u>	Location:	



40 Quart Planetary Floor Mixers

The Perfect Mix of Value. Performance & Durability

Features front mounted touch pad control panel with 60-minute digital timer!









Model

□ SP40

Standard Features

- Powerful custom built 2 HP motor
- Gear-driven, high-torque transmission
- Heat-treated hardened steel alloy gears & shafts
- Three fixed speeds
- Permanently lubricated transmission
- Thermal overload protection
- Front-mounted touch pad controls with 60minute digital timer and last-batch recall
- Removable stainless steel, interlocking bowl guard with built-in fully welded ingredient chute
- Interlocked bowl lift
- Rigid cast iron body
- Industry standard #12 attachment hub
- NSF approved enamel gray paint
- 6-foot cord and ground plug

Standard Accessories/Attachments

- 40 qt stainless steel bowl (#304 series)
- Aluminum flat beater
- Stainless steel wire whip
- Aluminum spiral dough hook
- Non-slip rubber feet

Warranty

Two year parts and labor


Optional Accessories/Attachments


- Seismic flange kit
- Polycarbonate splash shield insert
- Slicer/shredder/grater for #12 hub
- Meat grinder for #12 hub
- Stainless steel flat beater
- Stainless steel spiral dough hook
- 20 qt adapter kit
- Extended warranty


To select options, see complete list on back ck

Approved by:	Date:
,	

(66) 40 Quart Planetary Floor Mixers







UNIT: INCHES (CM)

Drawings available through KCL at www.kclcad.com.

SPECIFICATIONS												
Model	Motor	Volts Amps	Amne	Transmission Type	Capacity	Controls	Agitator Speeds (RPMs)			Attachment Speeds (RPMs)		
			Allips				1st	2nd	3rd	1st	2nd	3rd
SP40	2 HP	220/60/1* 208/60/3*	12 7	Gear	42 qt 40 liter	Front-mounted digital controls & timer	74	132	272	52	92	190

Cord & Plug: Attached 6-foot flexible 3-wire cord with molded plug fits a grounded receptacle. Single phase NEMA L6-30P 🕥 Three phase NEMA L15-20P 🕥 *Specify voltage when ordering

DIMENSIONS | SHIPPING INFORMATION

Carton reinforced for shipping. The weight and dimensions of this reinforced carton are included below and may vary from shipment to shipment.

This product ships on a pallet. Freight class 85.

Model	Base Foot Print	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight	
SP40	25.25" W x 24.5" D	25.25" W x 30.5" D x 51.5" H	550 lbs	46" W x 48" D x 65" H	653 lbs	
	(64 cm x 62 cm)	(64 cm x 77 cm x 131 cm)	(250 kg)	(122 cm x 122 cm x 165 cm)	(296 kg)	

Mixer is constructed of a rigid cast iron body with front-mounted controls and 60-minute digital timer with last-batch recall. Mixer has 2 HP custom built motor with overload protection and gear-driven, high torque permanently lubricated transmission consisting of heat-treated hardened steel alloy gears and shafts. Mixer comes with 40 qt. stainless steel bowl, aluminum flat beater, stainless steel wire whip, aluminum dough hook and non-slip rubber feet. Interlocked with removable stainless steel bowl guard with fully welded ingredient chute. Mixer has #12 attachment hub and interlocked bowl lift. Mixer is NSF and ETL listed. Two year parts and labor warranty.

OPTIONAL MIXER ACCESSORIES AND HUB ATTACHMENTS

(S/S) bowl ☐ XXBEAT-40 Alum. flat beater ☐ XXBEAT-40SS S/S flat beater ☐ XXHOOK-40 Alum. dough hook ☐ XXWHIP-40 S/S wire whip ☐ XXHDWHIP40-4 Heavy-duty 4 mm S/S wire whip ☐ XXHDWHIP40-5 Heavy-duty 5 mm S/S wire whip XXSCRP-40 Scraper with mounting kit

hook, beater and whip

☐ XXSEISMIC KIT-MD Seismic kit

☐ XXBOWL-40 40qt stainless steel

☐ XXBGSHIELD-40 Bowl guard shield

MIXER:

HUB: ■ XVSGH 9" Slicer/Shredder/Grater housing only (no plates included-must select from plates listed on this sheet) ☐ XASP Adjustable slicing plate (for vegetables only) ☐ XPH Plate holder -*only 1 required Shredding Plates: ☐ XSP332* 3/32" (2.3 mm)■ XSP316* 3/16" (4.7 mm)☐ XSP14* 1/4" (6.3 mm)■ XSP516* 5/16" (7.9 mm)☐ XSP12* 1/2" (12.7 mm)☐ XGP* **XXACC20-40** Adapter kit - 20 qt bowl, Grating plate

☐ XBTRUCK-40 Heavy-duty bowl truck

- ☐ XMCA-SS Meat grinder assembly (Polished stainless steel cylinder, worm gear, ring, and s/s pan. Includes knife, 3/16" plate, and pusher) ☐ XXCK Chopper knife for XMCA-SS Chopper Plate Sizes Available:
- ☐ CP02-12 1/16" (2 mm) ☐ CP04-12 5/32" (4 mm) ☐ CP05-12 3/16" (5 mm) ☐ CP06-12 1/4" (6 mm) ☐ CP08-12 5/16" (8 mm) ☐ CP10-12 3/8" (10 mm)☐ CP12-12 1/2" (12 mm)□ CP14-12 9/16" (14 mm)
- ☐ CP00-12 Stuffing plate
- XST12 1/2" Stuffing tube (pork) ☐ XST34 3/4" Stuffing tube (hog)
- ☐ FACTORY INSTALLED OPTION: XXCORR-40 Correctional package,
- includes tamper resistant external fasteners. **□** EXTENDED WARRANTY
- SP-XD4060 Extended warranty for SP40 mixer, extends factory warranty to 3 years. Available only at time of purchase.

2153 Dryden Rd., Dayton, OH 45439 | 937-299-5493 | 800-347-5423 | Fax: 937-299-4147 | www.globefoodeguip.com

(16 mm)

(18 mm)

☐ CP16-12 5/8"

☐ CP18-12 11/16"