OVENS



VC55G SERIES DOUBLE DECK GAS CONVECTION OVEN WITH REMOVABLE DOORS

Item #



Model VC55GD Shown with optional casters









SPECIFICATIONS

Double section gas convection oven, Vulcan Model No. VC55GD. Stainless steel front, sides, top and legs. Independently operated stainless steel doors with double pane windows. Non-sag insulation applied to the top, rear, sides, bottom and doors. Porcelain enamel on steel oven interiors measures 29"w x 221/8"d x 20"h. One interior oven light per section. Five nickel plated oven racks per section measure 281/4" x 201/2" with grab-and-go front cut out. Eleven position nickel plated rack guides with positive rack stops. One 50,000 BTU/hr. burner per section. 100,000 total BTU/hr. Electronic spark igniters. Furnished with a two speed 1/2 H.P. oven blowermotor per section. Oven cool switch for rapid cool down. 120 volt, 60 Hz, 1 ph power supply required. 6' cord and plug. 7.7 amps total draw per section.

Exterior Dimensions:

40"w x 40"d (includes motor & door handles) $37\frac{1}{4}$ "d (includes motor only) x $68\frac{3}{4}$ "h on 8" legs.

CSA design certified. NSF listed.

SPECIFY TYPE OF GAS WHEN ORDERING. SPECIFY ALTITUDE WHEN ABOVE 2,000 FT.

□ **VC55GD** Solid state temperature dial controls adjust from 150° to 500°F with digital display

from 150° to 500°F with digital display enhancement. 5-hour timer with audible alarm.

STANDARD FEATURES

- Independently operated lift-off stainless steel doors with double pane windows.
- On-board diagnostics for easy servicing
- Stainless steel front, sides and top.
- Five nickel plated grab-and-go oven racks with eleven rack positions.
- Painted legs.
- 5-hour timer with digital display enhancement.
- Cool-to-the-touch handles.
- 50,000 BTU/hr. burner.
- Electronic spark igniter.
- ½ H.P. two speed oven blower-motor. 120/60/1 with
 6' cord and plug. 7.7 amps total draw.
- Oven cool switch for rapid cool down.
- Porcelain enamel on steel oven interior.
- 3/4" rear gas connection with combination gas valve / pressure regulator and safety solenoid system.
- One year limited parts and labor warranty.
- Three year limited warranty on doors.

OPTIONS

Stainless steel legs.
Casters.

☐ Second year extended limited parts and labor warranty.

ACCESSORIES

	Extra oven rack(s).	
\Box	Pack hanger	

ш	nack	nanger.	

	Stainless	steel	drip	pan.
--	-----------	-------	------	------

- ☐ Flexible gas hose with quick disconnect and restraining device. Consult price book for available sizes.
- $\hfill\square$ Down draft flue diverter for direct vent connection.





VC55G SERIES DOUBLE DECK GAS CONVECTION OVEN WITH REMOVABLE DOORS


INSTALLATION INSTRUCTIONS


- A combination gas valve/pressure regulator and safety solenoid system is included in this unit. Natural gas is 5.0" W.C., Propane gas is 10.0" W.C.
- An adequate ventilation system is required for commercial cooking equipment. Information may be obtained by writing to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02289. When writing, refer to NFPA No. 96.
- These units are manufactured for installation in accordance with ANSZ223.1 (latest edition), National Fuel Gas Code. Copies may be obtained from American Gas Association Inc.,


Accredited Standards Committee Z223, 400 N. Capitol St. NW, Washington, DC 20001 or the Secretary Standards Council, NFPA, 1 Batterymarch Park, Quincy, MA 02169-7471.

4. Clearances:	Combustible	Non-combustible
Rear	0"	0"
Right Side	2"	0"
Left Side	1"	0"

5. This appliance is manufactured for commercial installation only and is not intended for home use.







							WEIGHT			
MODEL		DEPTH (INCLUDES		BTU/HR.	TOTAL		WITH & PACK			UT SKID KAGING
NO.	WIDTH	HANDLES)	HEIGHT	PER OVEN	BTU/HR.	ELECTRICAL	LBS.	KG	LBS.	KG
VC55G	40"	40"	68¾"	50,000	100,000	120/60/1	778	352	666	302



a division of ITW Food Equipment Group LLC

P.O. Box 696 ■ Louisville, KY 40201 ■ Toll-free: 1-800-814-2028 ■ Local: 502-778-2791 ■ Quote & Order Fax: 1-800-444-0602

