GRIDDLES & BROILERS



VHP SERIES HEAVY DUTY GAS HOT PLATE



Model VHP636







SPECIFICATIONS

Exterior Dimensions:

_____ wide x 313/8" deep x 12" working height

CSA Design Certified. NSF Certified.

SPECIFY TYPE OF GAS WHEN ORDERING. SPECIFY ALTITUDE WHEN ABOVE 3,999 FT.

□ VHP212 12" wide □ VHP424 24" wide □ VHP636 36" wide □ VHP848 48" wide

STANDARD FEATURES

- Stainless steel sides, control panel, top trim and backsplash.
- Full width pull out crumb tray.
- Heavy duty cast iron top grates.
- 30,000 BTU/hr. (27,500 BTU/hr. for LP gas) open burners with lift-off heads.
- Standing pilot ignition system.
- One infinite heat control valve for each burner.
- 4" adjustable legs.
- ¾" NPT rear gas connection and gas pressure regulator.
- One year limited parts and labor warranty.

OPTIONS

- ☐ Cutting board.
- □ Condiment rail.
- □ Plate rail.
- ☐ Stainless steel stand with undershelf and casters.
- ☐ Step-up burners. Rear burners elevated 4".



a division of ITW Food Equipment Group LLC

P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602



VHP SERIES HEAVY DUTY GAS HOT PLATE

INSTALLATION REQUIREMENTS:

- A gas pressure regulator supplied with the unit must be installed.
 Natural Gas 5.0" (127 mm) W.C. Propane Gas 10.0" (254 mm) W.C.
- An adequate ventilation system is required for commercial cooking equipment. Information may be obtained by writing to the National Fire Protection Association, 1 Batterymarch Park, Quicy, MA 02169, www.NFPA.org. When writing refer to NFPA No. 96.
- These units are manufactured for installation in accordance with National Fuel Gas Code, ANSI-Z223.1/NFPA #54 (latest edition).
 Copies may be obtained from The American Gas Association Accredited Standards Committee Z223, @ 400 N. Capital St. NW,


Washington, DC 20001, or the Secretary Standards Council, NFPA, 1 Batterymarch Park Quincy, MA 02169-7471.


NOTE: In the Commonwealth of Massachusetts


All gas appliances vented through a ventilation hood or exhaust system equipped with a damper or with a power means of exhaust shall comply with 248 CMR.


4.	Equipment clearance:	Non-Combustil	oles Combustibles
		Sides Back	Sides Back
	Standard	0" 0"	13" 6"
	Step-Up	0" 0"	13" 9"

5. This appliance is intended for commercial installation only and is not intended for home use.









MODEL	WIDTH	DEPTH	OVERALL HEIGHT*	WORKING HEIGHT*	NO. OF BURNERS	TOTAL BTU/HR. NATURAL GAS	TOTAL BTU/HR. PROPANE GAS	APPROX SHIP WT. (LB/KG)
VHP212	12"	313/8"	165/8"	12"	2	60,000	55,000	95 lbs./43 kg
VHP424	24"				4	120,000	110,000	165 lbs./74 kg
VHP636	36"				6	180,000	165,000	265 lbs./119 kg
VHP848	48"				8	240,000	220,000	310 lbs./140 kg

^{*}These are nominal dimensions and can vary by +1.75" with adjustable legs.



a division of ITW Food Equipment Group LLC

P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602