Ashland PolyTrap 4800 Series Grease Interceptors

PolyTrap[®] Grease Interceptor

The next

generation

in grease

removal technology.

No rust, corrosion,

seamless and

easy to ship. The

PolyTrap® 4800

Series product line is

approved by PDI and

listed by IAPMO and

UPC. The PolyTrap[®]

is available in a

multitude of sizes and

varieties for virtually

any application you

require.





Serviceable Bulk Head Fittings available in 2" and 3".



"D" Ring gaskets on covers.



All Units include flow control, shipped inside.



PDI Certified, IAPMO and UPC listed.



Shown in grey to illustrate baffle design.

PolyTrap® unique features include:

- Scientifically placed, removable baffles.
- Flow control device.
- Complete inlet and outlet connections with standard female NPT threads.
- D-ring sealing gasket between cover and tank.
- Matching cover with low pressure bolts in stainless steel.
- Easy-to-read installation instructions.
- Strong and durable, yet light in weight to make handling and installation less demanding.
- Products can ship via UPS.



UPC Listed by IAPMO and many local and state authorities



• Certified to the exacting standards of PDI.

• **Listed** by other local code authorities and national standards groups such as **IAPMO** and **UPC**.

• PolyTrap® is Superior to metal, fiberglass, or specially treated materials that are promoted as "preventing corrosion". PolyTrap® grease interceptors include a completely integrated surface guaranteed not to corrode, chip, peel or leach.


- Leak-proof, seamless constructed tank, manufactured with highquality material that provides enhanced stiffness in combination with impact resistant properties.
- **Lightweight**, easy to handle and install yet durable and sturdy to withstand the most rigorous applications of the plumbing industry.
- The unique resin used allows for use in applications requiring high temperature continuous service. No comparable material like it.
- Smooth, non-stick surface allows for easier and more complete cleaning, **Stay's Clean Looking**.
- Surfaces discourage bacteria build-up.
- High value for you the customer.
- Fast Delivery, in stock.
- Can be used on floor or in ground flush to floor.
- Can be shipped anywhere for very low cost compared to metal competitors.


Options and Considerations for ordering

- All dimensions are nominal and may vary from table.
- 4800 Series models include flow control device.
- Matte finish on all covers to reduce slipping.
- Special HD Diamond Plate cover over-lays are available for pedestrian traffic areas.
- All units include removable baffle and internal air-relief.
- * Check on code approval status & availability.



DATA ON DIMENSIONS & SPECIFICATIONS





Model Number		4804	4807	4810	4815	4820	4825	4835	4850	75*
Flow Rate G.P.M.		4	7	10	15	20	25	35	50	75
Grease Capacity (lbs.)		8	14	20	30	40	50	70	100	150
Approximate Dimensions (inches)	Length (A) Width (B) Height (C)	15 10 9.5	20 14.5 11	23 14.5 12	23 19.5 13	29 19.5 14	32.5 19.5 17	32.5 22 18	37 25 18	44 25 24
Top of unit to center of inlet/ outlet (D)		2	3.25	3.5	3.5	3.5	4	4	4	4
Nom. Wall Thickness (in.)		3/16	3/16	3/16	3/16	3/16	3/16	3/16	3/16	3/16
Approximate Weight (lbs.)		10	15	18	25	30	35	40	50	64
Standard Inlet/Outlet (in.)		2	2	2	2	2	3	3	3	3
Liquid Holding Capacity (gal)		2.3	5.6	7.3	12.1	17.6	24.8	30.0	40.5	61.8

^{*} This size not recognized yet by PDI/UPC/IAMPMO



World Wide Factory Sales and Distribution

PH. 419.836.2300

PH. 800.541.8004

Fax. 419.836.4140

email: polytraps@amplex.net

web: ashlandpolytraps.com

Ashland[®] Trap Distribution

Company

UPC Listed by IAPMO and many local and state authorities



Restaurants

Cafeterias

Fast Food Establishments

Hospitals

Nursing Home Kitchens

Hotels and Resorts

Food Processing Plants

Meat Processing Plants

Industrial Plants

Residential



Made in the U.S.A.