



# STAR-MAX® 15 Ib. ELECTRIC FRYER Model 301HLF

#### Features/Benefits:

- ★ Star's #1 selling 15 pound electric fryer offers excellent frying flexibility and fits almost any countertop requiring minimal space.
- ★ A 15 lb. lift-out nickel plated steel kettle for easy removal of grease or other cooking oils.
- ★ NEW longer lasting, heavy-duty metal knobs.
- ★ Immersion-type tubular heating elements provide even heat distribution and swing up design makes cleaning a snap.
- ★ Snap-action thermostat ranges from 200°F to 375°F and provides quick response to temperature change.
- ★ High-limit safety thermostat, on-off switch and indicator light provide safe and easy operation.
- ★ Two large nickel plated steel mesh side hanging baskets (5-5/32"W x 5-3/32"D x 10-11/16"L) provide continuous flow of product during peak periods
- ★ All stainless steel cabinet for maintenance free operation.
- ★ Heavy-duty 4" adjustable legs to match the height of other Star-Max equipment in your line.

### **Applications:**

Star-Max® single pot electric fryer has a wide variety of frying capabilities and is perfect for today's diverse menu selections. No matter what the menu items; onion rings, fries, chicken or fish, Star-Max electric fryer cooks food sealing in the flavor.

### **Quality Construction:**

Star's electric fryer features a control housing with indicator light, adjustable snap-action thermostat, hi-limit safety thermostat and immersion type elements are standard. Housing swings up to allow 15 lb. fat capacity kettle to be removed. Fryers operate on 208 or 240 volts with a 6' cord and plug.



Star-Max® electric fryer is covered by Star's **TWO YEAR** parts and labor warranty.



Model 301HLF










## Star Manufacturing

# Model 301HLF



Performance Data						
Model No.	Pre-Heat to 350°F (177°C)	Fat Capacity	Pounds of French	Watts Per Hour To		
			Fries Per Hour	Maintain 350°F (177°C)		
301HLF	5 Minutes	15 lbs. (6.8 kg)	28 lbs. (12.7 kg)	430		

### **Dimensions & Weight**

	Overall Dimensions						
	(A)	(B)	(C)	Cooking Surface		Approximate Weight	
	Width	Depth	Height	Height		Installed	Shipping
Model	Inches	Inches	Inches	lbs.		lbs.	lbs.
No.	(cm)	(cm)	(cm)	(kg)		(kg)	(kg)
301HLF	18	20	17	11		37	47
	(45.7)	(50.8)	(43.2)	(27.9)		(16.8)	(21.3)
	Fat Container			Foam Compartment			
	Width	Depth	Height	Width		Depth	Height
Model	Inches	Inches	Inches	Inches		Inches	Inches
No.	(cm)	(cm)	(cm)	(cm)		(cm)	(cm)
301HLF	13	12	3-3/4	16		13	3-3/8
	(33.0)	(30.4)	(9.5)	(40.6)		(33.0)	(8.6)

Legs adjustable 4" to 5-3/8" (10.2 cm to 13.7 cm)

### **Electrical Data**

Model No.	Rated Wattage 208V 240V	Nominal Amps 208V 240V	NEMA Plug
301HLF	4130 5500	19.9 22.9	6-30P

### **Typical Specifications**

Electric fryer has a stainless steel body. A 200° - 375° (93°C - 190°C) adjustable thermostat and a hi-limit safety thermostat, and a separate on-off switch are standard. A one piece nickel plated, lift out 15 lb. (6.8 kg) capacity steel kettle and 4" nickel-plated die cast legs are standard. Unit has a tubular type, two position, swing-up element with a rated wattage of 5500 watts on 240 volts. Two side mounted nickel plated, perforated steel mesh baskets are provided as standard. A 6 ft. (182.9 cm) lead-in cord and plug with a NEMA 6-30P. UL listed to US and Canadian standard. UL Classified to NSF STD 4. Printed in the U.S.A.

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice. While Star Manufacturing exercises good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.

**Star Manufacturing -** 10 Sunnen Drive - P.O. Box 430129 - St. Louis, MO 63143-3800 Phone: (314) 678-6303 - FAX: (314) 781-5445 - www.star-mfg.com