

BARS – TAKEAWAY OUTLETS – RESTAURANTS – HOTELS – HEALTH FACILITIES



J 100 Ultra AUTOMATIC JUICER

2 WAYS OF USING YOUR JUICER

Continuous pulp ejection

Ejection chute sending continuous flow of pulp directly into bin under worktop.





2 Pulp ejected into container

7.5 Qt large-capacity translucent pulp container
















UNIQUE INNOVATION

AUTOMATIC JUICERS

J 80 Ultra • J 100 Ultra



Patented automatic feed tube with a diameter of 3 inches for continuous throughput and hassle-free juicing.







AUTOMATIC JUICERS

J 80 Ultra • J 100 Ultra



Product benefits:

- Automatic: the unique design of the feed tube does away with the need for a pusher! You can now produce high volumes of top-quality juice quickly and effortlessly!
- **High power, low noise levels:** the powerful, heavy-duty motor operates at a speed of 3450 rpm, meaning that the juice oxidizes less quickly. The resulting juices are particularly smooth and bursting with flavour. The noise levels of the J 80 Ultra/J 100 Ultra are so low that they can be used right in front of the customer.
- **Practical:** the drip tray can hold up to 10 oz of liquid, meaning that your worktop stays clean.
- Large-capacity pulp container! the 6.5-Quart (J 80 Ultra) or the 7.5-Quart (J 100 Ultra) translucent container slots neatly under the ejector spout, to avoid pulp splashing onto the worktop.

The J 100 Ultra can be used in two ways:

- 1. Continuous pulp ejection: ejection chute sending a continuous flow of pulp directly into a bin beneath the worktop.
- 2. Pulp ejected into a container: 7.5-Quart large-capacity translucent pulp container.
- Centrifugal juicer basket: the basket can be removed (no special tool required) for easy cleaning.



Users:

Bars, takeaway outlets, restaurants, hotels, canteens, health related establishments



In short:

They have all the qualities you could ask for in a juicer: fast, resilient, efficient, and top-quality juice.



Video available on: www.robotcoupeusa.com



INDUCTION MOTOR

- Heavy-duty motor designed to withstand intensive use for greater reliability and a longer lifespan.
- Ball bearing-supported motor for ultra-quiet, vibration-free operation.
- Direct-drive motor:
 - extra power
 - no belt
- Maintenance-free: no wearing parts (no brushes)
- Stainless-steel motor shaft



		Electrical characteristics			Dimensions Inches				Weight (lbs)	
		Speed (rpm)	Power (W)	Voltage* (A)	А	В	С	D	Net	Gross
	J 80 Ultra	3450	700	120V/60/1	20	21	9.25	6.25	26	28
	J 100 Ultra	3450	1000	120V/60/1	23.5	21	9.25	10,25	32	34

^{*} Other voltages available

J 80 Ultra J 100 Ultra J 100 Ultra J 100 Ultra C C

Robot Coupe U.S.A., Inc.

264 South Perkins, Ridgeland, MS 39157 1-800-824-1646 (601) 898-8411 FAX: (601) 898-9134 email: info@robotcoupeusa.com

www.robotcoupeusa.com

Distributor



We reserve the right to alter at any time without notice the technical specifications of this appliance. None of the information contained in the document is of a contractual nature. Modifications may be made at any time.

© All rights reserved for all countries by : ROBOT-COUPE s.N.C.