Project:	AIA#
Item:	
Location:	SIS#
Approved:	

# **BAR EQUIPMENT - BACK BAR REFRIGERATOR**

BB24HC Glass Door Food Rated Hydrocarbon Series

MODELS: BB24HC-1-FG-B BB24HC-1-FG-S

# 3 Year Parts/Labor Warranty Additional 4 Year Compressor Warranty

# BIVIRACE-AIR

## **CABINET CONSTRUCTION**

- Black or stainless steel exterior
- Stainless steel interior
- Full electronic control
- Stainless steel top
- Two (2) epoxy coated shelves
- 120° stay open door feature, with automatic stay open feature
- Field reversible doors
- LED lighting
- Certified for open food product
- Four (4") heavy duty casters 2 with locks
- Balanced, forced air refrigeration system provides rapid chilling of product

### **OPTIONS & ACCESSORIES**

- Wine model (40°-60° models)
- Underbar model option
- Additional epoxy coated shelves
- Additional shelf clips

### **REFRIGERATION SYSTEM**

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil
- Maintains product temperature between 36°F and 38°F




















MODEL	BB24HC-1-FG-B	BB24HC-1-FG-S
EXTERNAL DIMENSIONAL DATA		
Width Overall	24"	24"
Depth Overall with Handle	30 1/8"	30 1/8"
Height Overall with 4" Casters	37 3/4"	37 3/4"
Number of Doors	1	1
Depth With Door Open 90°	50 3/4"	50 3/4""
Door Opening (in)	28" x 19 3/4"	28" x 19 3/4"
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	7.66	7.66
Internal Width Overall (in)	20"	20"
Internal Depth Overall (in)	22 1/4"	22 1/4"
Internal Height Overall (in)	29 1/2"	29 1/2"
Number of Shelves	2	2
Number of 1/2 Kegs	1	1
ELECTRICAL DATA		
Full Load Amperes 115/60/1	2.0	2.0
REFRIGERATION DATA		
Horsepower	1/6	1/6
Capacity (BTU/Hr)*	1094	1094
WEIGHT DATA		
Gross Weight (Crated lbs)	200 lbs	200 lbs
Height - Crated	46"	46"
Width - Crated	27"	27"
Depth - Crated	32"	32"

# **Bar Equipment-Back Bar Refrigerator** Glass Door Food Rated

Models: BB24HC-1-FG-B, BB24HC-1-FG-S



### **ELECTRICAL CONNECTION**

















Unit pre-wired at factory and include 8' long cord and plug set.



