

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

DELI/BAKERY CASE

MODEL: CDR5HC-1-W

CDR5HC Deli/Bakery Case Refrigerator Hydrocarbon Series





CABINET CONSTRUCTION

- Exterior has white powder coated galvanized steel
- Stainless steel interior with mirrored end caps
- Sliding glass, removable doors
- Curved front glass
- Full electronic control with various set points
- · LED lighting with on and off switch
- Electrical outlet for scale
- Adjustable shelves for better product display
- Price tag molding standard
- Open food rated

OPTIONS & ACCESSORIES

- Dry case (add -D to refrigerated models)
- 3" casters
- 5" casters

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- · Hot gas condensate evaporator
- · Hot gas defrost system
- · Maintenance free condenser
- Refrigerator maintains product temperatures between 33°F to 41°F
- Direct sunlight should be avoided
- Tested to 75°F and 55% relative humidity




3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com



MODEL	CDR5HC-W	
EXTERNAL DIMENSIONAL DATA		
Width Overall	60 1⁄4"	
Depth Overall	35 ⁴⁷ / ₆₄ "	
Height Overall	48 %16"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	17	
Internal Width Overall (in)	56 ¹³ ⁄32"	
Internal Depth Top & Middle Overall (in)	14 ³¹ / ₃₂ "	
Internal Depth Overall Bottom (in)	24 7/32"	
Internal Height Overall (in)	38 ⁴³ / ₆₄ "	
Number of Shelves	2	
ELECTRICAL DATA		
Full Load Amperes	5.0	
REFRIGERATION DATA		
Horsepower	1/4	
Energy Consumption	6.8 kw-hr/24 hrs	
SHIPPING DATA		
Gross Weight- Crated	571 lbs	
Height - Crated	58 5⁄16"	
Width - Crated	67 ¹³ ⁄ ₆₄ "	
Depth - Crated	40"	

Deli/Bakery Case Refrigerator Model: CDR5HC-W



*ELECTRICAL CONNECTION



120/60/1

Units pre-wired at factory 120/60/1 and include 8' long cord and plug set.

