

Cuisine Series Heavy Duty Front-Fired Hot Top Range

Models

- C836-10
- C0836-10
- C0836-10M



Model C836-10
Range with Two
Front-Fired Hot Tops

Standard Features

- 37,500 BTU per 18" (457mm) Front Fired Hot Top
- Full-range valve control - 3 per 18" (457mm) section
- Removable lids and rings
- Stainless steel front and sides
- Stainless steel front rail w/ position adjustable bar
- 1-1/4" NPT front gas manifold
- Can be connected individually or in a battery
- 6" (152mm) high stainless steel stub back
- 6" (152mm) chrome steel adj. legs
- Stainless steel oven interior w/ removable porcelain bottom
- 40,000 BTU burner
- Chrome plated rack with four positions, 1 per oven
- Fully insulated oven interior
- 100% safety oven pilot
- Oven thermostat control - 150°-500°F (66°-260°C)

Options & Accessories

- Stainless steel back
- Range base convection oven (add RC)
- Porcelain oven interior in lieu of stainless steel interior - NC
- Single or double deck high shelf or back riser
- Modular unit with legs and shelf (suffix M)
- Modular unit w/o legs on Refrig. Base (change suffix M to PC)
- Stainless steel intermediate shelf for cabinet base
- Stainless steel door(s) for cabinet base units
- Continuous plate shelf, 48-72" for battery installations
- Gas shut-off valves - 3/4", 1", 1 1/4" NPT (Specify)
- Gas regulator: 3/4"- 1 1/4" NPT (Specify)
- Gas flex hose w/ quick disconnect 3/4", 1", 1 1/4" (Specify)
- Stainless steel legs (set of four)
- Flanged feet set of four
- Set of (4) polyurethane non-marking swivel casters w/front brakes.
- Extra oven rack
- Stainless steel burner box top interior

Specifications

U.S. Range Cuisine 36" (914mm) wide Heavy Duty Range Series. Model _____ with total BTU/hr rating of _____ when used with natural/propane gas. Stainless steel front and sides. 6" (152mm) legs with adjustable feet.

Ovens - One piece oven door. Stainless steel oven interior with a heavy-duty, "keep-cool" door handle. Standard oven comes with a thermostat with a temperature range from 150° (low) to 500°F (66°-260°C). One chrome plated oven rack for standard ovens and three for convection ovens.


18" (457mm) Section Front-Fired Hot Tops - 12,500 BTU/hr each burner with three per section.

Note: Range-based convection oven models can be located in the middle of a battery, banked back-to-back with other equipment, and can be positioned against a wall

NOTE: Ranges supplied with casters must be installed with an approved restraining device.



Cuisine Series Heavy Duty Front-Fired Hot Top Range



| Model # | Description | Total BTU (NAT. Gas) |
|-----------|--|----------------------|
| C836-10* | Two (2) - 18" (457mm) FFHT - Standard Oven | 115,000 |
| C0836-10 | Two (2) - 18" (457mm) FFHT - Cabinet Base | 75,000 |
| C0836-10M | Two (2) - 18" (457mm) FFHT- Modular | 75,000 |

FFHT = Front Fired Hot Top

* Add Suffix "RC" for Convection Oven Base 1/3 Hp motor 120V 60Hz 0.6 Amps c/w Nema 5-15P cord & plug

| Combustible Wall Clearance | |
|----------------------------|------------|
| Sides | Back |
| 6" (152mm) | 6" (152mm) |

| Individual Burner Ratings (BTU/hr) | | |
|------------------------------------|----------------------------|--------|
| Burner | NAT. | PRO. |
| 18" Front Fired Hot Top | 12,500 (3 per 18" Section) | |
| Std. Oven | 40,000 | 35,000 |
| Conv. Oven | 37,000 | 35,000 |

| Interior Dimensions: In (mm) | | | |
|------------------------------|--------------|--------------|----------|
| Product | Height | Width | Depth |
| Standard Oven | 13-1/2(323) | 26-1/4 (667) | 29 (737) |
| Convection Oven | 13-1/2(323) | 26-1/4 (667) | 25 (635) |
| Cabinet Base | 20-1/2 (521) | 32-1/4 (819) | 31 (787) |

| Gas Pressure | NAT. | PRO. |
|-----------------------------|-------|--------|
| Minimum Supply | 7" WC | 11" WC |
| Manifold Operating Pressure | 6" WC | 10" WC |
| Gas Manifold 1-1/4" NPT | | |

Welbilt reserves the right to make changes to the design or specifications without prior notice.

Garland Commercial Ranges Ltd.
1177 Kamato Road,
Mississauga, Ontario
L4W 1X4 CANADA

General Inquires 1-905-624-0260
USA Sales, Parts and Service 1-800-424-2411
Canadian Sales 1-888-442-7526
Canada or USA Parts/Service 1-800-427-6668

www.garland-group.com
6986
12/18