

E24 Series Heavy Duty Electric Hot Plate

Models

E24-12H



E24-12H

Standard Features

- Standard Features
- · Stainless steel front and sides
- Removable porcelain enameled spill-over bowls
- 4" (102mm) Sanitary legs
- · Heat-On indicator lamps
- Two 8 1/2" (216mm) 2.1 kW elements
- Infinite switch with "Heat On" indicator light for each element
- One-Year limited parts & labor warranty (USA & Canada only)

Options & Accessories

Stainless steel back

Note: Stands are available see form # CS24/CSD

Specifications

The Garland E24-12H electric heavy duty counter hot plate is designed and engineered for high volume fast food operations, providing fast preheat, high production and versatility with quality results. Designed as freestanding units or to bank with other E24 series equipment or with G24 series gas counter equipment providing flush fronts and backs. Stainless steel front and sides, 15" (381mm) wide x 29" (710mm) deep x 11 1/4" (286mm) high. Elements tilt up to facilitate removal of porcelain enameled spillover bowls for easy cleaning. Infinite heat switch with indicator light controls each 8 1/2" (216mm) diameter 2.1 kW element, both switches have "OFF" settings. Indicator lights are mounted on switch panel and show when element is "ON". Front access panel is removable.








General Inquires 1-905-624-0260 USA Sales, Parts and Service 1-800-424-2411 Canadian Sales 1-888-442-7526 Canada or USA Parts/Service 1-800-427-6668


www.garland-group.com 6840 12/18







Garland products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland will not provide service, warranty, maintenance or support of any kind other than in commercial applications.



[737mm]

29"

NOTE: Add 4" (102mm) to height if sanitary legs are used.

Loading Chart										
	Total Kw Load	Nominal Amperes Per Line								
Model		3 Phase						Single Phase		
		240V			208V			240V	208V	
		Х	Υ	Z	Х	Υ	Z	2401	2001	
E24-12H	4.2	15.2	8.8	8.8	17.5	10.1	10.1	17.5	20.2	

Export voltage available on request – Specify wiring required

kW loadings are reduced on 220 volt systems.

Standard wiring 240 volt (220/240) or 208 volt (197/219) single or three phase - Specify which is required

Model	Overall Dimensions	Shipping Wt. Lb/kg			
Model	Height	Width	Depth	3 Shipping Wt. Lb/kg	
E24-12H	11-1/4" (286mm)	15" (381mm)	29" (737mm)	60/27	

L	Installation Clearances			
	Side	Rear		
	1.5" (38mm)	1.5" (38mm)		

Welbilt reserves the right to make changes to the design or specifications without prior notice.

