

# GF Sentry Series Infra-Red Salamander Broiler

Project \_\_\_\_\_  
 Item \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 CSI Section 11400  
 Approved \_\_\_\_\_  
 Date \_\_\_\_\_

## Models

- GFIR36M
- GFIR48M
- GFIR60M
- GFIR36CM



Model GFIR36M  
 Infra-Red Broilers With  
 Pull Out Broiling Rack

## Standard Features

- Range Mount Models – stainless steel front, sides, top, backsplash, & bottom w/heat shield
- Counter: model GFIR36CM stainless steel front, sides, & top – C/W 4" (102mm) legs
- 1/2" NPT gas inlet: range mount, standard on top; counter models standard at rear, All models can be ordered with top or rear gas connections, specify at time of order
- Two (2) 20,000 BTU (5.86 kw) atmospheric infra-red burners, each controlled with Hi-Lo valve
- Sentry flame failure protection
- Gas Regulator
- Fixed position broiling rack with flat or easy view tilt position, roll in, roll-out back
- Large capacity removable grease pan

## Options & Accessories

- Stainless steel main back.
- Stainless steel main bottom – GFIR36CM
- Brackets for wall mounting and stainless steel bottom w/heat shield – GFIR36CM
- Interconnecting gas piping for range mount


## Specifications

Range mount gas infra-red salamander broiler. Two 20,000 BTU (5.86 kw) atmospheric burners, each with a Hi-Lo valve. Fixed position, roll-in, roll out broiling rack with flat or tilt positions. 34" (864mm) wide x 19 3/8" (492mm) deep x 73 11/16" (1872mm) high when mounted on a range. Refer to drawing for detail specifications. 40,000 BTU (11.72 kw) total. Natural or propane gas. Available as counter top or wall mounted models – CFIR36CM.



GF Sentry Series Infra-Red Salamander Broiler

# GF Sentry Series Infra-Red Salamander Broiler



| Model #  | Description                                             | Width                | Use With GF Series Model | Shipping Information |         | Entry Clearances |                |
|----------|---------------------------------------------------------|----------------------|--------------------------|----------------------|---------|------------------|----------------|
|          |                                                         |                      |                          | Cu FT                | Lbs/Kg  | Crated           | Uncrated       |
| GFIR36CM | Counter/Wall Mount                                      | 34"<br>(864mm)       | N/A                      | 21                   | 170/77  | 31"<br>(787mm)   | 21"<br>(533mm) |
| GFIR36M  | Range Mount                                             | 35-1/2"<br>(900mm)   | GF/GFE36                 | 38.2                 | 200/91  | 31"<br>(787mm)   | 21"<br>(533mm) |
| GFIR48M  | Center Mounted Broiler With Extended Flue On Both Sides | 47-1/4"<br>(1200mm)  | GF/GFE48                 | 60.6                 | 230/105 | 31"<br>(787mm)   | 21"<br>(533mm) |
| *GFIR60M | Broiler With 24"(610 mm) Flue Riser And Shelf           | 59-1/16"<br>(1500mm) | GF/GFE60                 | 60.6                 | 260/118 | 31"<br>(787mm)   | 21"<br>(533mm) |

\*Note: for range models, salamanders are standard on right but available on the left as an option.  
For raised griddle/broiler models, salamanders are only available on left side of the range.

| Non-Combustible Clearance                 |           |      |           | Manifold Operating Pressure |                |
|-------------------------------------------|-----------|------|-----------|-----------------------------|----------------|
| For use in non-combustible locations only |           |      |           | Natural                     | Propane        |
| Sides                                     | 0 (in/mm) | Back | 0 (in/mm) | 4"WC(10mbar)                | 10"WC (25mbar) |

Gas input ratings shown here are for installations up to 2,000 ft. (610m) above seal level. Specify altitudes over 2,000 ft.

Garland/U.S. Range products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland / U.S. Range will not provide service, warranty, maintenance or support of any kind other than in commercial applications

Please specify gas type when ordering.

Welbilt reserves the right to make changes to the design or specifications without prior notice.

**Garland Commercial Ranges Ltd.**  
1177 Kamato Road,  
Mississauga, Ontario  
L4W 1X4 CANADA

**General Inquires 1-905-624-0260**  
USA Sales, Parts and Service 1-800-424-2411  
Canadian Sales 1-888-442-7526  
Canada or USA Parts/Service 1-800-427-6668

[www.garland-group.com](http://www.garland-group.com)  
6934  
12/18