

WARING
COMMERCIAL®



Season food with your favorite herbs and spices, then vacuum seal.



Prepare and cook multiple portions ahead of time.



Perfect for all restaurants and off-premises cooking. Just sear quickly to finish and serve.



16 AND 25 LITER | THERMAL CIRCULATORS

INTEGRATED BATH SYSTEMS



WSV16

WSV25

- Built for sous vide cooking and re-thermalizing
- Water bath temperature accuracy of +/- .5°C/1°F
- 5 programmable memory stations & 99-hour timer
- Capacitive touch control enables you to quickly set or adjust the cooking temperature
- Integrated hose system to easily and safely remove water from reservoir
- All stainless steel construction
- Temperature range from 95°F – 194°F (35°C – 90°C)

WSV16: 16-Liter (4.2 Gallons) Capacity

WSV25: 25-Liter (6.6 Gallons) Capacity



16 AND 25 LITER | THERMAL CIRCULATORS

INTEGRATED BATH SYSTEMS

POUCH RACK

FOR IDEAL POSITIONING



ITEM	ELECTRICAL	LISTINGS	OUT OF BOX WEIGHT	OUT OF BOX DIMENSIONS L x W x H	CORD LENGTH	WARRANTY
WSV16	120 V, 1560 W, 13 Amps	cETLus, ETL Sanitation	15.9 lb.	13.5" x 14.25" x 10.5"	3.5 Feet	Limited 1 Year Motor
WSV25	120 V, 1560 W, 13 Amps	cETLus, ETL Sanitation	20 lb.	23.5" x 14.25" x 10.5"	3.5 Feet	Limited 1 Year Motor

ORDERING INFORMATION	#STD. PKG.	GIFTBOX WEIGHT	CUBIC FEET	BOX DIMENSIONS L x W x H	UPC	CASE PKG.	MC WEIGHT	MC DIMENSIONS L x W x H	MBC
WSV16 – 16L Sous Vide	1	18	1.16	18" x 16.875" x 13.125"	040072037634	1	22 lb.	18.375" x 17.5" x 13.875"	10040072037631
WSV25 – 25L Sous Vide	1	26	3.43	25" x 16.875" x 13.125"	040072037627	1	28 lb.	25.5" x 17.5" x 13.875"	10040072037624

ITEM	DESCRIPTION	UPC
WSV16DH	Drain hose for WSV16 & WSV25	040072083549
WSV16LRK	Rack lift for WSV16	040072083532
WSV16RK	Rack for WSV16	040072083525
WSV16CVR	Cover for WSV16	040072083518
WSV25LRK	Rack lift for WSV25	040072083501
WSV25RK	Rack for WSV25	040072083495
WSV25CVR	Cover for WSV25	040072083488



@waringcommercial

waringcommercialproducts.com

©2018 Waring Commercial
314 Ella T. Grasso Avenue, Torrington, CT 06790
Tel. 800-492-7464 • Fax 860-496-9008

18WC051872