eikon°



eikon[™] e3

Model:

e3



Standard Features

- Advanced Cooking Technology® combines two heat technologies of convection and microwave with a rotating turntable for fast, even heating of food product
- Up to five (5) times faster than conventional cooking methods
- "Ventless* Cooking" capability through standard built-in catalytic converter with full protein capability
- Two (2) rack positions
- Ability to use a standard, ¼ size metal baking pan while in convection mode
- Automatic voltage detection (U.S. only)
- Cool to touch door exterior
- MenuConnect™ Ethernet connection for remote uploads to menus and diagnostics

*Local codes prevail. These are the "authority having jurisdiction" as stated by the National Fire Protection Association, Inc., in NFPA96-1994.


Specifications

Construction

- 430 stainless steel casework and 304 stainless steel interior cavity
- Easy side panel access to internal components
- Easily accessible, front facing air filter

EasyToUCH™ Control Panel

- Icon driven, color touch screen control panel with the capability of storing up to 1,024 multi-stage recipe programs
- Each program offers up to six (6) stages with programmable cooking times, microwave power settings and user instructions for each stage
- Self diagnostics capability to monitor components
- Easy menu updates or data transfer via USB memory stick
- Multi-languages available





Air in the oven cavity is cleaned by being drawn through the catalytic converter* (1) by the convection fan (2) and then passes over the heating element and is circulated into the oven cavity (3) at the set temperature.







Merrychef U.S.A 1111 N. Hadley Rd. Ft. Wayne, IN 46804 Tel: 888.417.5462 Fax: 800.285-9511 E-Mail: info@merrychefusa.com

www.merrychef.com MCF 6026 4/27/16









Overall Size			
Height	21.7"	551 mm	
Width	23.5"	598 mm	
Depth (overall with handle)	24.5"	622 mm	
Depth (door open 90 degrees)	37.0"	939 mm	
Weight	138 lbs	62.5 kg	
Shipping Weight	168 lbs	76.2 kg	
Shipping Box Size	30 x 30.3 x 33.85"	760 x 770 x 860 mm	
Oven Cavity Dimensions			
Height	12.56"	319 mm	
Width	13.07"	332 mm	
Depth	12.8"	325 mm	
Wall Clearance			
Тор	2"	50.8 mm	
Sides	2"	50.8 mm	
Electrical Specifications			
Phase	1 ph		
Voltage	208 / 240		
Frequency	60Hz		
Amperage Requirement	30 amp	G •	
Plug	NEMA 6-30P		
Cord Length	6 ft	(/	
Power Consumption	max 4700W	NEMA C 200	
Power Output (Microwave)	700/1000W	NEMA 6-30P	
Power Output (Convection)	3 kW		

*○*Merrychef

Specifications		
Preheat Time	15 minutes	
Control System	easyToUCH™, iconic symbol touch screen control panel	
Cooking Stages	6	
Total Cooking Programs	1,024	
Maximum Cooking Time	60:00 (10:00 x6 Stages)	
Defrost	No	
Microwave Distribution System	Rotating Active Antenna	
Magnetron(s)	1	
Display	Touchscreen	
Interior Light	No	
Automatic Voltage Sensor	Yes	
USB & MenuConnect [™] Software	Yes	
Temperature Range	Off, 212°F - 482°F	
Temperature Increments	1°F (from 212°F upwards)	
Air Filter	Yes - removable	
Fan Speed	High	
Microwave Power	0%(off), 5%-100%	
Microwave Power Increments	1% (from 5% upwards)	
Rack	No	
Rack Positions	2	
Turntable	Yes	
Stackable	No	
Warranty	1 year parts and labor	
Accessories in Box		
Round Cast Teflon Coated Tray	2 units	
Handle	1 unit	
Turntable Disk	1 unit	
Bottle Cleaner	1 unit	
Bottle Shield	1 unit	
Spray Triggers	2 units	
Operator Manual /Cleaning Instructions	1 unit	
USB Key	1 unit	
Cool down Tray	1 unit	





For further information on Merrychef products and service or advice on which machine suits you best please contact your sales representative or visit our website at www.merrychef.com.

Specifications subject to change without notice.

Merrychef U.S.A 1111 N. Hadley Rd. Ft. Wayne, IN 46804 Tel: 888.417.5462 Fax: 800.285-9511 E-Mail: info@merrychefusa.com

www.merrychef.com MCF_6026 4/27/16

