



☐ PA0015



- Sink and Bowl: 16Ga.304 stainless steel
- Top: Backsplash is 16Ga.304 stainless steel
- Legs: 1.625"(42.5mm) S/S legs with 1.579"(40.1mm) S/S adjustable feet

16GA.304S/S sink 57"X57"X43.75"H
3 tub: 18"X18"X14", 18" left and 18" right drainboard
18GA.S/S leg and S/S socket, S/S bullet foot
with "H" shape 20GA.leg bracing
3.5" drain basket included, wooden skid packing, NSF approved

- 16Ga. 304 Stainless steel.
- 14"(355mm) deep tub with 3/4"(19.05mm) covered radius tub corners
- 10.276"(261mm) backsplash with tile ledge for easy installation
- Raised 1.614"(41mm) diameter rolled edge
- 3-1/2"(88.9mm) drain with basket strainer included
- 1-.625"(42.5mm) S/S legs with 1.579"(40.1mm) S/S adjustable feet
- "H" shape 20GA. leg bracing

- 1-1/8"(28.6mm) faucet holes on 8"(203mm) centers
- 3-1/2"(88.9mm) waste drain opening

Technical drawing of a table showing dimensions and annotations:

- Top surface width: 1447 [57"]
- Distance from top edge to center of front leg: 203 [8"]
- Distance from top edge to center of side leg: 2-ø28 [ø 1 1/8"]
- Distance from top edge to center of rear leg: 356 [14"]

