

## Features

### Airpot Coffee Brewer

- Brews 3.8 to 6.8 gallons of perfect coffee per hour.
- Brews directly into 1.9 to 3 liter airpots.
- Convenient airpots keep coffee hot and fresh for hours.
- Airpots are easily transported to remote meeting rooms, breakfast bars, etc.
- Pourover model available (CW15-APS).
- Pourover feature included on automatic models.
- Gourmet funnel model available for use with heavier throw weights of coffee.
- Digital timer enables users to make brew cycle adjustments from the front panel.
- International electrical configurations available.



*Model CWTF APS  
with Airpot\**

*(airpot not included)*

Dimensions: 23.6" H x 9" W x 18.5" D

\* International models may vary in appearance.

## Related Products

For current specification sheets and other information, go to [www.bunnomatic.com](http://www.bunnomatic.com).

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

### Easy Clear® EQ-17-TL

Product No. : 30200.1000

Dimensions:

12<sup>7</sup>/<sub>16</sub>" H x 2<sup>1</sup>/<sub>2</sub>" W x 3" D  
31.6 cm H x 6.35 cm W x 7.62 cm D



### Easy Clear® ED-17-TL

Product No. : 30201.1001

Dimensions: 8<sup>1</sup>/<sub>4</sub>" H x 2<sup>3</sup>/<sub>16</sub>" Dia.

20.95 cm H x 5.87 cm Dia.

### Paper Filter Pack

Product No. : 20115.0000

Packed per case: 1,000

Dimensions: 4<sup>1</sup>/<sub>4</sub>" Base x 2<sup>3</sup>/<sub>4</sub>" Sidewall

10.8 cm Base x 6.98 cm Sidewall



### 2.2 liter Airpot

Product No. : 28696.0002

Capacity: 74 oz. (2.19 L)



### 2.5 liter Airpot

Product No. : 13041.0001

Capacity: 84 oz. (2.48 L)



### APR5

#### 5 Position Airpot Rack

Product No. : 25371.0002

Capacity: 5 Airpots

*(also available in 2 & 3 position models)*

### Gourmet C Funnel

Product No.: 34559.0000 (7.12 inch width)

34559.0001 (7.62 inch width)



- Universal design - handle may be moved to appropriate side
- Allows brewing with heavier throw weights of coffee.

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

ITEM#

PROJECT

DATE

## International Model

*CWA-APS  
CWTF-APS  
CWTF35A-APS*

## Model

*CW APS  
CWT APS  
CWTF APS  
CDBCF APS*

## BUNN®

### Corporate Offices

1400 Stevenson Drive  
Springfield, Illinois 62703

**Phone**

800-637-8606

217-529-6601

**Fax**

217-529-6644

**Technical Services**

800-286-6070

**Internet**

<http://www.bunnomatic.com>

### Western Regional Office

16431 Carmenita Road,  
Cerritos, California 90701

**Phone**

562-926-0764

**Fax**

562-926-0858

### Canadian Office

280 Industrial Parkway South  
Aurora, Ontario, L4G 3T9

**Phone**

905-841-2866

**Fax**

905-841-2775

**Patents Apply**



## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
CW15-APS*	23001.0000	120	12.7	1320	1520	3.9 gal./hr.	5.0	28 lbs. (12.7 kg)	Yes
CWT15-APS	23001.0003	120	12.7	1320	1520	3.9 gal./hr.	5.0	29 lbs. (13.2 kg)	Yes
CWT15-APS**	23001.0017	120	15	1320	1520	3.9 gal./hr.	5.2	38 lbs. (17.3 kg)	Yes
CWT35-APS	23001.0018	120/240	16.2	3500	3700	6.8 gal./hr.	5.0	30 lbs. (13.6 kg)	No
CWTF15-APS	23001.0006	120	12.7	1320	1520	3.9 gal./hr.	5.0	33 lbs. (15.0 kg)	Yes
CWTF15-APS***	23001.0051	120	12.7	1320	1520	3.9 gal./hr.	5.0	33 lbs. (15.0 kg)	Yes
CWTF20-APS	23001.0007	120	20	1800	2000	5.5 gal./hr.	5.0	32 lbs. (14.6 kg)	No
CWTF35-APS	23001.0008	120/240	16.2	3500	3700	6.8 gal./hr.	5.0	33 lbs. (15.0 kg)	No
CWTF35-APS***	23001.0052	120/240	16.2	3500	3700	6.8 gal./hr.	5.0	33 lbs. (15.0 kg)	No

\*Pourover model. \*\*Stainless steel funnel. \*\*\*Model has gourmet funnel.

**Electrical:** CW15-APS, CWT15-APS & CWTF15-APS - require 2-wires plus ground service rated 120V, single phase, 60Hz. CWTF20-APS - requires 2-wires plus ground service rated 120V, single phase, 60Hz. CWT35-APS & CWTF35-APS - require 3-wires plus ground service rated 120/240V, single phase, 60Hz.

**Plumbing:** 20-90 psi (69-621 kPa). Supplied with 1/4" (6.4 mm) male flare fitting.

