



T&S BRASS AND BRONZE WORKS, INC. 2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690

Model No.

EC-3102-SMT8V05

Item No.

Travelers Rest, SC: 800-476-4103 • Simi Valley, CA: 800-423-0150 • Fax: 864-834-3518 • www.tsbrass.com

Travelers Rest, SC: 800-476-4103 • Simi Vall	ley, CA	: 800-423-0150	• Fax: 864-834-3518 • www.tsprass.com
	ITEM NO.	SALES NO.	DESCRIPTION
-	1	B-0199-08- N05	0.5 GPM VR Spray Device, 13/16-27 Male
-	2	017195-45	Angled Sensor w/ Cable
	3	018251-45	ChekPoint 8" C-C SMT Deck Plate
-	4	018541-45	M4 x 20mm, SS, Torx VR FH Screw
	5	018249-45	Handle
	6	018248-45	Temperature Limit Stop
	7	EC-SMT	Above Deck Thermostatic Mixing Valve w/ Handle
71	8	016297-45	Inlet Hose, Faucet, 1/2" NPSM-F x 1/4" NPSM-F
2	9	016647-45	ChekPoint Module (Blue)
	10	EC-FILTER	•
)	11	002534-25	Close Nipple, 1/2" NPT
	12	5EF-0002	Double Gang, Plug-in AC Transformer
	13	016167-45	Supply Hose, 1/2" NPSM Female x 1/2" NPSM Female
	14	5EF-0005	Supply Hose, 9/16-24 Female x 1/2" NPSM
		8	A Maximum of (8) ChekPoint Faucets can be Hardwire Connected and Powered by EC-HARDWIRE ChekPoint Hardwire AC Transformer. (Sold Separately)
	J		
di.	10		Label for Flow Control Switch Settings
	(11)		is Located on Inside of Back Cover.
018543-45 015425-45			Flow Control Switches are Located Inside Module Housing in Black Box Next to Battery Compartment. *Switches are Set to DEFAULT Position: - Auto Time Out = 15 Seconds - Shut Off Delay = 1 Second - Auto Flush = OFF
VR Screw L-Key VR Aerator Key			Remove (4) Screws and Back Cover to
*Available Water Flow Control Selection - Auto Time Out: 15 sec, 30 sec, 45 sec - Shut Off Delay: 1 sec, 10 sec, 15 sec - Auto Flush (30 Seconds After Every	sec, 60 ec, 30	sec	
Product Specifications:	<u>.</u>		Product Compliance:
Chrome Plated Brass Electronic Faucet: Single Hole Deck M Spout w/ 8" Centers Deck Plate, Above Deck Side Mount			ASIVIE AT 12.10.17 CSA B 125.1
SDULL W/ O CETTERS DECK FILLE. ADOVE	K		NSF 61 - Section 9
Adjustable Thermostatic Mixing Valve w	// Integ	ral Check Val	ves, NSF 372 (Low Lead Content) ernal Flow ANSI A117.1 (ADA)
	/ Integ trol Mo	ral Check Val odule with Inte	ves, NSF 372 (Low Lead Content)