SC200 SERIES - SELF CONTAINED ICE MACHINE

STILL THE ONLY CUBE OF ITS KIND.



The KOLD-DRAFT SC200


- Stores 125 lbs of ice -Best in Class
- ADA Compliant: 31.4"H without legs, fits under 34" countertops
- Ideal for any undercounter or bar application
- Front breathing design allows for installation in tight spaces
- Produces unique 1.25" x 1.25" x 1.25" hard, square cubes
- Slow melting cube perfect for cocktails and beverages



Dimensions/Weight								
Description	D	Ship Weight						
	W	D	Н	Ship vveigne				
Air Cooled (without legs)	out legs) 26" (66cm)		31.4" (79.8cm)	207lb (94kg)				
With Legs	26" (66cm)	28.6" (72.6cm)	37.4" (100cm)	207lb (94kg)				

Recommended Operating Requirements:	MIN.	MAX.		
Room Temp.	45°F (7°C)	90°F (32°C)		
Water Temp.	45°F (7°C)	90°F (32°C)		
Voltage 208-230	210V	250V		
Voltage 115	104V	126V		
Potable Water Pressure	5 PSIG (0.034 kPa)	100 PSIG (689 kPa)		

SC200 Series Daily Capacities: Lbs. of ice per 24 hours per unit											
Model Number	Electrical Volt/ Cond Hz/Ph	Condenser	nser Cube Size	Ice Capacity 24 Hours Ibs. (kg)		Energy Input 90°F/70°F	-Tier	Water Use gal/100# (I/kg) 90°F/70°F		Min.	Max. Fuse
		Condenser		70°F (21°C) / 50°F (10°C) Ambient/Water	90°F (32°C) / 70°F (21°C) Ambient/Water	kWh/100# (kJ/kg)	riei	Potable	Condenser	Amp	Size Amps
SC201	115/60/1	Air Cooled	Full Cube	150 (68.04)	119 (53.98)	8.71 (691.28)	Ι	29.56 (2.47)	n/a	6	15



Plumbing:

1/2" FIP potable water inlet 3/4" FIP ice bin drain

1/2" FIP ice maker drain

.88" Diameter electrical connection

Exterior Finish:

Corrosion-resistant stainless steel exterior with plastic door and bin liner









KOLD-DRAFT • 101 Corporate Woods Parkway, Vernon Hills, IL 60061 (800) 840-9577 • info@kold-draft.com • www.kold-draft.com

an Ali Group Company



The Spirit of Excellence