

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Drojoct	
Project	•

Model # : Item # :

Available W/H :

Approval :

Mega Top Unit - Slide Lid

____ FEATURES & BENEFITS =___

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

• Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Cold Bunker system


Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

Stainless steel cabinet construction

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a **22 gauge** stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

- Sturdy, clean stainless steel shelving Shelves are the most important part of cleanliness as they come in direct contact with food. Only the PRO series uniquely provides stainless steel shelving.
- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail
- Spring assisted heavy duty gravity hinge
- Removable insulated slide-back lid Removable hood and slide-back lid are easy to clean while providing a better view of the top opening.
- High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.







LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

- Refrigerator holds 33°F ~ 39°F for the best in food preservation
- Lifetime guaranteed heavy duty hinges and handles
- Built to maintain NSF standard temperatures in 100°F ambient

4 week lead time applies

PST-48-18-N-SL	2	15	2	18	1/5	6.5	264	481/4 x 34 x 391/8
Model	Swing Doors	CU./FT.	#of Shelves	#of Pans	HP	AMPS	Crated Weight (lbs.)	$L \underset{(inches)}{x D^{*}x H^{\dagger}}$
						Refrigeran		U. S. A

* Depth does not include 3" for cutting boards and 1" for rear spacers. † Height does not include 5-3/8" for caster height.

Model : PST-48-18-N-SL

Qty :

Food Prep Tables PRO Series

Mega Top Unit - Slide Lid

Model: PST-48-18-N-SL

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	(i) NEMA 5-15P				
Full Load Amperes	6.5				
Compressor HP	1/5				
Feed Wires with Ground	3				
Cord Length (ft.)	10				
Refrigerant	R-290				
DIMENSIONAL DATA					
Ext. Length Overall (in.)	481/4 (1225mm)				
Ext. Depth Overall (in.)*	34 (864mm)				
Ext. Height Overall (in.) ⁺	391/8 (993mm)				
# of Doors	2				
# of Shelves	2				
# of Pans	18				
# of Hood	1				
Net Capacity (cu. ft.)	15				
Shelf Size (in.)	21 x 17				
Net Weight (lbs.)	255				
Gross Weight (lbs.)	264				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 3" for cutting boards and 1" for rear spacers.

+ Height does not include 5-3/8" for caster height.

WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

STANDARD FEATURES

- Anti-corrosion coated evaporator
- · Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- Door locks standard
- 4 week lead time applies

OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: M727800100
- Stainless steel double overshelf: TSOS-4R
- ** Please allow lead time for shipping. Please call factory for more details to place an order.

(GERMAN

KNIFE







lurbo air

PLAN VIEW

(unit : inch)







SIDE VIEW

Turbo Air : 800-627-0032 **GK** : 800-500-3519

- Warranty : 800-381-7770 AC : 888-900-1002
- Turbo air Texaking