

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Sandwich / Salad Unit - Drawers

Food Prep Tables
PRO Series

Model: PST-48-D4-N

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



___ FEATURES & BENEFITS =__

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

- Digital temperature control & monitor system
 Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.
- Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Stainless steel cabinet construction

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a **22 gauge** stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail
- Easy, removable hood & hood lid for cleaning
- Insulated hood & hood lid
- Built to maintain NSF standard temperatures in 100°F ambient
- Refrigerator holds 33°F ~ 39°F for the best in food preservation
- Lifetime guaranteed heavy duty handles
- 4 week lead time applies











_									Intertex Intertex -	
	Model	Swing Doors	Drawers	CU./FT.	#of Shelves	#of Pans	HP	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
	PST-48-D4-N	-	4	12	-	12	1/5	6.5	347	481/4 x 30 x 37

(unit: inch)

Model: PST-48-D4-N

ELECTRICAL DATA							
Voltage	115/60/1						
Plug Type	① NEMA 5-15P						
Full Load Amperes	6.5						
Compressor HP	1/5						
Feed Wires with Ground	3						
Cord Length (ft.)	10						
Refrigerant	R-290						
DIMENSIONAL DATA							
Ext. Length Overall (in.)	481/4 (1226mm)						
Ext. Depth Overall (in.)*	30 (762mm)						
Ext. Height Overall (in.) †	37 (940mm)						
# of Doors	-						
# of Drawers	4						
# of Shelves	-						
# of Pans	12						
# of Hood	1						
Net Capacity (cu. ft.)	12						
Net Weight (lbs.)	265						
Gross Weight (lbs.)	347						

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


STANDARD FEATURES

- · Anti-corrosion coated evaporator
- · Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- 4 week lead time applies


OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, ½" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Removable food cover: RCT-48
- · Stainless steel double overshelf: TSOS-4R
- ** Please allow lead time for shipping. Please call factory for more details to place an order.

PLAN VIEW



TOP VIEW



SIDE VIEW

Ver.20191101













■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002











^{*} Depth does not include 2" for door handle & rear spacers.

[†] Height does not include 5-3/8" for caster height.