

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Proi	iant	•
Proj	ICCI	

Model # : Item # :

Qty :

Extra Deep Glass Side Panel

Available W/H :

Approval :

Vertical Open Display Cases

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating prush that moves up and down daily to remove excess buildup outward and away.



W/ Security cover (optional)



TOM-GODXS-N

____ FEATURES & BENEFITS ____

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Modern design

By integrating great contours with durable structures, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics. Safety reinforced tempered glass front shield and side walls optimize the merchandiser's display effects of fresh salads, sandwiches, desserts and beverages. Its elegant contemporary euro design will enhance any store application.

- Designed to enhance impulsive sales
 Ideal for eye-catching displays and convenient access with fast service in high traffic area.
- Standard back-guard improves airflow
- Energy saving night curtain standard
- Optional security cover available
- Foamed with polyurethane, high-density cell insulation (CFC free)
- Perforated interior back wall and top for improved airflow
- Front air intake and rear air discharge
- Stainless steel exterior and interior
- 8 week lead time applies

Model	CU./FT.	# of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H$ (inches)
TOM-60DXS-N	18.9	4	3/4 x 2	15.5	822	60 x 333/8 x 787/8

* Depth does not include 1-5/8" for safety bar and 1-1/8" for rear bumper

Model : TOM-60DXS-N

Vertical Open Display Cases

Model : TOM-60DXS-N

ELECTRICAL DATA			
Voltage	115/60/1		
Plug Type	• NEMA 5-20P		
Full Load Amperes	15.5		
Compressor HP	3/4 x 2		
Refrigerant	R-290		
DIMENSIONAL DATA			
Net Capacity (cu. ft.)	18.9		
Ext. Dimension (L x D^*x H) (in.)	60 x 333/8 x 787/8		
Int. Dimension (L x D x H) (in.)	571/4 x 211/4 x 483/4		
# of Shelves	4		
Shelf Size (L x D) (in.)	571/4 x 16		
Power Cord Length (in.)	118 1/8		
Net Weight (Ibs.)	635		
Gross Weight (lbs.)	822		

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 1-5/8" for safety bar and 1-1/8" for rear bumper.

2 Year Parts and Labor Warranty WARRANTY : Additional 3 Year Warranty on Compressor

STANDARD FEATURES


- Simple plug-in installation
- Patented self-contained system, no plumbing required
- · Solar powered digital thermometer
- Digital electronic thermostat with defrost control
- LED interior lighting
- 8 week lead time applies

Recommended operating conditions


TOM models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product.

OPTIONAL ACCESSORIES


- 1.6" caster: CAS16WBT00 (non-brake)
- 4" caster, 1/2" diameter & 13 TPI: G8F6500101 (non-brake), G8F6500201 (w/ brake)
- 6" leveling seismic leg (1/2", 13 TPI): 30221M0700
- Security cover: SC-60-DXB, SCM-60-DXB, SCS-60-DX
- Price tag channel: P60DX000ZK (57"L)







FRONT VIEW



Ver.20191107



- **Turbo Air** : 800-627-0032 **Warranty** : 800-381-7770
- **GK**: 800-500-3519
- **AC** : 888-900-1002

lurbo air

KNIFE

(GERMAN)

