

REFRIGERATOR MANUFACTURER
Turbo air
 more durable, efficient, beautiful

4184 E. Conant St.
 Long Beach, CA 90808
 Tel. 310-900-1000
 Fax. 310-900-1077
www.turboairinc.com

Project :

Model # :

Item # :

Qty :

Available W/H :

Approval :


Vertical Air Curtain

Open Display Merchandisers

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



TOM-60EB-N

Model : TOM-60EB-N

FEATURES & BENEFITS

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Modern design

By harmonizing curvature and rigidness, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics. The glass front shield optimize the merchandiser's display effects of fresh salads, sandwiches, desserts and beverages.

Designed to enhance impulsive sales

Ideal for eye-catching displays and convenient access with fast service in high traffic area.

White coated galvanized steel interior

White coated galvanized steel solid shelves

Energy saving night curtain standard

Standard back-guard improves airflow

Foamed with polyurethane, high-density cell insulation (CFC free)

Perforated interior back wall and top for improved airflow

Front air intake and rear air discharge

NATURAL
Refrigerant

SP
SANITATION C

SP
US

2 YEAR
WARRANTY

5 YEAR
WARRANTY

| Model | CU./FT. | # of Shelves | HP | AMPS | Crated Weight (lbs.) | L x D x H (inches) |
|-------------------|-------------|--------------|----------------|-------------|----------------------|---------------------------|
| TOM-60EB-N | 30.6 | 4 | 3/4 x 2 | 15.5 | 842 | 60 x 297/8 x 811/8 |

Vertical Air Curtain

Open Display Merchandisers

Model : TOM-60EB-N

| ELECTRICAL DATA | |
|---------------------------|-----------------|
| Voltage | 115/60/1 |
| Plug Type | ☎ NEMA 5-20P |
| Full Load Amperes | 15.5 |
| Compressor HP | 3/4 x 2 |
| Refrigerant | R-290 |
| DIMENSIONAL DATA | |
| Net Capacity (cu. ft.) | 30.6 |
| Ext. Length Overall (in.) | 60 (1524mm) |
| Ext. Depth Overall (in.) | 29 7/8 (759mm) |
| Ext. Height Overall (in.) | 81 1/8 (2061mm) |
| # of Shelves | 4 |
| Power Cord Length (in.) | 118 1/8 |
| Net Weight (lbs.) | 648 |
| Gross Weight (lbs.) | 842 |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

- **WARRANTY :** 2 Year Parts and Labor Warranty
Additional 3 Year Warranty on Compressor

■ STANDARD FEATURES

- Simple plug-in installation
- Patented self-contained system, no plumbing required
- Solar powered digital thermometer
- Digital electronic thermostat with defrost control
- LED interior lighting
- Standard color comes in black only
- Price tag channel: P60E0000ZK (56 1/2" L)

■ Recommended operating conditions


TOM models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product. When used as a built-in, required clearance for the rear is 4" and the top is 5".

■ OPTIONAL ACCESSORIES

- 1.6" caster: CAS16WBT00 (non-brake)
- 4" caster, 1/2" diameter & 13 TPI: G8F6500101 (non-brake), G8F6500201 (w/ brake)
- 6" leveling seismic leg (1/2", 13 TPI): 30221M0700
- Security cover: SC-60-E (White), SC-60-EB (Black), SCM-60-E (White), SCM-60-EB (Black), SCS-60-E


PLAN VIEW

(unit : inch)



FRONT VIEW

Power Cord
(Back of the product)



SIDE VIEW

Ver.20191210



- Turbo Air : 800-627-0032 ■ GK : 800-500-3519
- Warranty : 800-381-7770 ■ AC : 888-900-1002

REFRIGERATOR MANUFACTURER
Turbo air

GERMAN
KNIFE

RADIANCE

HYDROBATION SYSTEM
Turbo air

Texaking