



## DIGITAL PORTION CONTROL SCALE

The Digital Portion Control Scale (SD1114) joins the exclusive CDN line of NSF® Certified **Master Scales Series** scales, providing foodservice kitchens unprecedented quality and value. Equipped with a small profile removable stainless steel platform and a heavy-duty food-safe ABS plastic case, this model offers a 11 pound capacity for accurately weighing a wide variety of items. The SD1114 features field calibration to ensure accuracy over time, an easy-to-read LCD display with selectable units, tare and data hold functionality, and battery status indication. It comes with an AC adapter to preserve battery life.



### SPECIFICATIONS

|                            |                                                                                                                                                                                                                                                        |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Measurement Range:</b>  | 11 lb/5 kg by lb:oz and kg.g                                                                                                                                                                                                                           |
| <b>Display Size:</b>       | 3.35 W x 0.866 H (in)/<br>8.5W x 2.2 H (cm)                                                                                                                                                                                                            |
| <b>Platform Size:</b>      | 5.35 W x 5.35 L (in)/<br>13.6 W x 13.6 L (cm), removable                                                                                                                                                                                               |
| <b>Product Dimensions:</b> | 5.90 W x 1.75 H x 7.87 D (in)/<br>15.0 W x 4.45 H x 20.0 D (cm)                                                                                                                                                                                        |
| <b>Resolution:</b>         | 0 lb:0.1 oz, 1 g                                                                                                                                                                                                                                       |
| <b>Power:</b>              | AC Adapter: 100-240 VAC 50/60 Hz<br>input, 9V DC (500mA) output, included<br>Batteries: two AAA 1.5V IEC LR03<br>alkaline, included                                                                                                                    |
| <b>Weight:</b>             | 18.5 oz/524 g                                                                                                                                                                                                                                          |
| <b>UPC:</b>                | 0 18436 00820 0                                                                                                                                                                                                                                        |
| <b>Other:</b>              | <ul style="list-style-type: none"> <li>• Selectable units</li> <li>• Overload indication</li> <li>• Battery status indication</li> <li>• On/off button</li> <li>• Auto-off after 2 minutes;<br/>disabled when the power<br/>adapter is used</li> </ul> |

### AVAILABLE

Now shipping



### FEATURES

- NSF® Certified
- Tare function
- Data hold
- Field calibration
- Removable stainless steel platform
- Batteries/power adapter

