KMS-1122MLJ 07/02/24 Item # 13253

WxDxH 22" x 181/8" x 311/4"

Shipping Dimensions 30^{1/2}" x 30" x 37"

Installation Dimension* SRK-12J / SRK-12J3 523/8" x 191/2" x 43"

Actual Dimension **SRK-12J / SRK-12J3** 50^{1/4}" x 17" x 28"



KMS-1122MLJ

Remote Air-Cooled Shown on optional Lancer 30" Dispenser





Features

ΔΙΔ#٠

- Individual crescent cube
- Stainless steel evaporator
- ► CycleSaver™ design CycleSave



- Up to 1151 lbs. of ice production per 24 hours
- · Durable stainless steel exterior
- EverCheck[™] alert system
- No heat, less noise
- · CFC / HFC Free Foam
- · R-404A Refrigerant
- Not recommmended for side-by-side application















Warranty:

3 Year Parts & Labor on entire machine. 5 Year Parts & Labor on Evaporator. 5 Year Parts on Compressor; air-cooled condenser coil.

Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

	ICE PRODUCTION		WATER USAGE		ELECTRICAL					
Condenser	Model	Air / Water Temp Lbs. per 24 hours 70°/ 50°F 90°/ 70°F		Potable Gal. per 100 lbs. 90°/ 70°F	Condenser Gal. per 100 lbs. 90°/ 70°F	kWh Used per 100 lbs. 90°/ 70°F	Voltage	Circuit Wires (including ground)	Refrigerant Charge Amount	Net / Ship Weight (lbs.)
Remote	KMS-1122MLJ with SRK-12J	1151	1075	16.0	N/A	4.2	115V/60/1*	4 [‡]	7.1 oz.	122 /152
Remote	KMS-1122MLJ with SRK-12J3	1151	1100	16.0	N/A	4.05	115V/60/3*	4	7.1 oz.	122 /152
* Voltage supply for KMS Ice Maker is										MS Ice Maker is

		LINE SETS - Brazing Required			TEMP RANGE	E ELECTRICAL					Supplied from the SHK hemote condenser			
Conde	nser	Model	25' Length	35' Length	55' Length	Ambient (Outdoor Use)	Voltage Range	Min. Circuit/ Max. Fuse Size	Amperage	Voltage	Circuit Wires (including ground)	Heat Rejection BTU/hr.	Refrigerant Charge Amount	Net / Ship Weight (lbs.)
Rem	note	SRK-12J	HS-0250 [†]	HS-0251 ⁺	HS-0252 [†]	-20 - 122°	187-253VAC	20A	11.6A	208-230V/60/1	4 [‡]	16,500	15 lb. 14 oz.	230 /275
Rem	note	SRK-12J3	HS-0250 [†]	HS-0251 [†]	HS-0252 [†]	-20 - 122°	187-253VAC	20A	10.5A	208-230V/60/3	4	17,300	15 lb. 14 oz.	230 /275

Line sets require refrigerant. If neutral is not available transformer kit (HS-5030) is required. Refer to instruction manual for installation and electrical requirements. See instruction manual for wiring diagram. Power cord not included. Must be hard-wired at site.

45 - 100°F


187-253V‡

• If GFCI is required, a GFCI breaker MUST be used in lieu of

10 - 113 PSIG

45 - 90°F

KM*Edae*™ Cube Dimensions*



- Allow 6" (15 cm) clearance at rear, sides, and top for proper air circulation and ease of maintenance and/or service should they be required.
- · Panels easily removed and all components accessible for service.

Operating Limits- KMS-1122MLJ

· Ambient Temp Range

Service- KMS-1122MLJ

Water Temp Range

Water Pressure

· Voltage Range

GFCI receptacle

Plumbing- kms-1122MLJ

- Icemaker Water Supply Line: Minimum 3/8" Nominal ID Copper Water Tubing or Equivalent
- · Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent

Service- SRK-12J(3)

- Allow 24" (61 cm) clearance in both front and rear for proper air circulation and ease of maintenance/service.
- For best performance the Remote Condenser should not be more than 33 feet above the icemaker or no more than 10 feet below it. These distances are measure from fitting to fitting.


Hoshizaki reserves the right to change specifications without notice

[‡] Voltage supply for KMS Ice Maker is supplied from the SRK Remote Condensel












REMOTE AIR-COOLED




SRK-12J(3) REMOTE CONDENSER






1/2" FIELD CONNECTIO SUCTION LINE 5/8" FIELD CONNECTION TIRE HARNESS CONNECTION 7/8" DIA. OPENING ICEMAKER WATER ICENAKER DRAIN OUTLET 3/4" FPT



REMOTE AIR-COOLED

SRK-12J(3) REMOTE CONDENSER

SRK-12J(3) Remote Condenser (Sold Separately) (W x D x H) 523/8 x 191/2 x 43 For Use with KMS-1122MLJ



Liquid Ref. Line Electrical Supply 7/8" Dia.Opening **Brazed Line Sets** Suction Ref. Line (Sold Separately) 25' HS-0250 35' HS-0251 55' HS-0252 Voltage supply for the KMS Ice Maker is supplied from the SRK Remote Condenser.